



**Tank Mounted Box with
Premium Control
Configuration and Ordering Form**

CUSTOMER		DATE	
ADDRESS		QUANTITY	
CONTACT		BOX POWER	110-220 VAC 24 VAC 24 VDC
PHONE		<i>The standard build is 110VAC, includes the temperature sensor, Quick Clamp mounting bracket and sensor cord grip.</i>	
EMAIL			

TYPE OF VALVE TO CONTROL	SOLENOID	CONTROLTEC BALL VALVE	power open, power close BALL VALVE	SPRING RETURN BALL VALVE

BOX CONFIGURATION – select option 1, 2 or 3 Holes are pre-cut Hole diameters = M20	QUICK SET BUTTON Option
---	--------------------------------








1. Customer to provide own conduit or cord grips
2. ControlTec provides one 2 hole grip for sensor & valve
3. ControlTec to supply both power & 2 hole grips



Pre-program up to 4 setpoints into control and change between them with each press of the button. Quick and convenient!

check box to select Quick Set Button

Standard Equipment	TANK BOX OPTIONS
---------------------------	-------------------------

 <p>Quick Clamp Mtg. Bracket</p> <p>Check Box to DELETE bracket</p>	 <p>Uni-Strut Mounting Nut mount to any Unistrut rail</p> <p>Check Box to INCLUDE</p>	 <p>Power Cords (prewired to control box)</p> <p>15 ft (4.5) 20 ft. (6 m) Check box to include cord</p>	 <p>ControlTec Ball Valve 15 ft. (4.3m) cord wired on site to box</p> <p>3/4" 1"</p>	 <p>ControlTec Ball Valve w/ extension for high moisture environments</p> <p>3/4" 1"</p>
--	--	--	--	---

Please use the space below to indicate anything special needed for this build:

--

NOTE: Buttons may not work in all browsers. For full functionality, download form and fill out in a .pdf viewer