



Tank Mounted Controls with Remote Communication Configuration and Ordering Form

CUSTOMER		DATE	
ADDRESS		QUANTITY	
CONTACT		BOX POWER	110-220 VAC 24 VAC 24 VDC
PHONE		<i>The standard build is 110VAC, includes the temperature sensor, Quick Clamp mounting bracket and sensor cord grip.</i>	
EMAIL			

TYPE OF VALVE TO CONTROL	SOLENOID	CONTROLTEC BALL VALVE	power open, power close BALL VALVE	SPRING RETURN BALL VALVE

BOX CONFIGURATION – select option 1, 2 or 3 Holes are pre-cut Hole diameters = M20, M25	QUICK SET BUTTON Option
--	--------------------------------








1. Customer to provide own conduit or cord grips
2. ControlTec provides one 3 hole grip for sensor, valve and communication wires
3. ControlTec to supply both power & 3 hole grips



Pre-program up to 4 setpoints into control and change between them with each press of the button. Quick and convenient!

check box to select Quick Set Button

Standard Equipment	TANK BOX OPTIONS
--------------------	------------------

				
Quick Clamp Mtg. Bracket Check Box to DELETE bracket	Uni-Strut Mounting Nut mount to any Unistrut rail Check Box to INCLUDE	Power Cords <i>(prewired to control box)</i> 15 ft (4.5) 20 ft. (6 m) Check box to include cord	ControlTec Ball Valve 15 ft. (4.5m) cord wired on site to box 3/4" 1"	ControlTec Ball Valve w/ extension for high moisture environments 3/4" 1"

Please use the space below to indicate anything special needed for this build:

NOTE: Buttons may not work in all browsers. For full functionality, download form and fill out in a .pdf viewer