CONTROLTEC

CELLARSTAR™

Economy Tank Mounted Box Configuration and Ordering Form

CUSTOMER		DATE	
ADDRESS		QUANTITY	
CONTACT		BOX POWER	○ 110-220 VAC ○ 24 VAC ○ 24 VDC
PHONE		***The standard build is 110VAC, includes the temperature sensor, Quick Clamp mounting bracket and sensor cord grip.***	
EMAIL			

TYPE OF VALVE TO CONTROL	SOLENOID	CONTROLTEC BALL VALVE	power open, power close BALL VALVE	SPRING RETURN BALL VALVE
	○	○	○	○

BOX CONFIGURATION – select option 1, 2 or 3
Holes are pre-cut Hole diameters = M20

○

1. Customer to provide own conduit or cord grips

○

2. ControlTec provides one 2 hole grip for sensor & valve



○

3. ControlTec to supply both power & 2-hole grips

Standard Equipment	TANK BOX OPTIONS			
Quick Clamp Mtg. Bracket ☐ Check Box to **DELETE** bracket	**UNISTRUT MOUNTING NUT** **mount to any Unistrut rail** ☐ Check Box to **INCLUDE**	**Power Cords** *prewired to control box* ○ **15 ft (4.3m)** ○ **20 ft (6m)** *Check box to include power cord*	**CONTROLTEC Ball Valve** *15 ft. (4.3m) cord wired on site to box* ○ **3/4"** ○ **1"**	**ControlTec Ball Valve with extension** for high moisture environments ○ **3/4 "** ○ **1"**

Please use the space below to indicate anything special needed for this build:

NOTE: Buttons do not work in all browsers. For full functionality, download form and fill out in a .pdf viewer

Email to ControlTec **PRINT FORM** **SAVE FORM**